

## Digital Display Aluminum Webster Hardness Tester

DW-20 series aluminum Webster hardness tester divided into DW-20, DW-20A, DW-20B three types, they are light and portable can be hold by one hand, do not need sample when testing, without high skill requirements.

It can do fast NDT test of work-piece on site and meet the needs of quality control and qualified rate, widely used in production test, acceptance inspection and products quality inspection of aluminum industries and many companies of windows, door and curtain wall, as well as in engineering quality inspection and technical supervision departments. It is a necessary device in raising qualification rate and saving cost.



## Models and Applications:

DW-20 Webster hardness tester is mainly used for inspection of aluminum alloy, tubes and plate,

▶ DW-20A type can be used to inspect industrial aluminum extrusions, plates or parts which of the thickness upper limit to 13 mm,

▶ DW-20B type for testing small aluminum profiles or aluminum profiles pipes which of the inner diameter is greater than 6 mm.

## **Technical Specifications:**

| Model                      | DW-20                             | DW-20A                  | DW-20B                 |  |
|----------------------------|-----------------------------------|-------------------------|------------------------|--|
| Measurement Range          | 0-20HW                            |                         |                        |  |
| Accuracy                   | 0.5HW                             |                         |                        |  |
| Accurate Measurement Range | 5-18HW                            |                         |                        |  |
| Test Materials             | Aluminum Alloy (1100-7075 series) |                         |                        |  |
| Resolution                 | 0.1HW                             |                         |                        |  |
| Hardness Conversion Range  | 25-110HRE, 58-131HV               |                         |                        |  |
| Spacimon Siza (mm)         | Thickness 0.4-6, Inner            | Thickness 0.4-13, Inner | Thickness 0.4-8, Inner |  |
| Specimen Size (mm)         | Diameter > 10                     | Diameter > 10           | Diameter > 10          |  |

## Packing List:

| Description                             | Qty | Description      | Qty |
|---|-----|------------------|-----|
| Main Unit                               | 1   | Carrying Case    | 1   |
| Standard hardness block                 | 1   | Warranty Card    | 1   |
| Special Wrench                          | 1   | Certificate      | 1   |
| AC Adapter                              | 1   | Operation manual | 1   |
| AAA battery (Take off when Ship by air) | 2   |                  |     |